




116.599

Cut Resistant Gloves Protector

Typhoon® fibre with a double dipped sandy nitrile coating



- Provides extreme blade cut resistance, EN 388:2016, level F (highest level).
- Excellent abrasion and tear resistance.
- Double dipped sandy nitrile coating for superior abrasion resistance.
- Thumb crotch reinforcement.
- Very flexible, dexterous and comfortable fit.
- Typhoon[®] is one of the strongest fibres in the world.
- Ideal for precision handling in oily conditions.
- OEKO-TEX[®] 100 Approved.

Standards and **Approvals**

























Suitable for:

Handling parts with sharp, rough edges | Handling sharp metal sheets | Cutting glass | Metal working and assembly operations etc.





Thumb base reinforcemen

CATEGORY:

Extreme-Fit Assembly Gloves

Cut Resistant Gloves

INDUSTRY:

Automotive

Building and Construction

Glass

Oil, Gas and Mining

Pulp and Paper

Steel and Metal

STANDARDS AND APPROVALS:

EN 420:2003 + A1:2009

EN 388:2016+A1:2018

ANSI/ISEA 105-2016

OEKO-TEX® Standard 100

CE Cat.II

PROTECTION AND RESISTANCE:

Abrasion Resistant

Cut Resistant

Puncture Resistant

Tear Resistant

FEATURES AND PROPERTIES:

Breathable

Precision

Thumb base reinforcement

PRODUCT DETAILS

Nitrile

Tight fit

Palm coated

Dry, Wet, Oil

7 | 8 | 9 | 10 | 11 | 12

Coating material:

Coating type :

Grip :
Glove fit :

Size :

Color: Black, Grey

Sales Units Per Bundle: 12

Sales Units Per Outer Case: 144

PACKING / TRANSPORT