



FEARLESS PERFORMANCE®



**115.9014**

Impact and Chemical Protective Cut Resistant Gloves



Bonded with 360° Anti-Cut Typhoon® Liner

- Nitrile offering liquid-proof barrier and protection against a wide range of chemicals and high abrasion-resistant durability.
- EN 374:2016/Type A high chemical resistance. The Nitrile coating offers ≥ 480 minutes of permeation time for n-Heptane found in oil based muds.
- High visibility green for maximum safety.
- Tested according to EN 388:2016 (mechanical and impact protection) and EN 374:2016 (chemical protection).
- Heat resistant up to 100°C for 15 seconds.
- Shorter version of 115.9013.

**Standards and Approvals**

**Suitable for:**

Oil & Gas: Upstream, Transportation, Downstream and Clean Up | Sewage/Draining Facilities | Water Treatment Facilities



Cut resistant



High visibility



Impact protection



Waterproof



Oil repellent

**INDUSTRY:**

- Chemical
- Janitorial
- Maintenance
- Oil Gas and Mining
- Waste/recycling

**STANDARDS AND APPROVALS:**

- EN 420:2003
- EN 388:2016
- EN 374:2016
- EN 407:2004
- CE Cat.III

**PROTECTION AND RESISTANCE:**

- Abrasion resistant
- Chemical protection
- Cut resistant
- Impact protection
- Waterproof
- Oil repellent
- Puncture resistant
- Tear resistant

**FEATURES AND PROPERTIES:**

- High visibility
- Seamless



**PRODUCT DETAILS**

Material :	Nitrile	Glove fit :	Loose fit
Liner material :	Typhoon®	Size :	8/M   9/L   10/XL   11/XXL   12/XXXL
Lining type :	Fully lined	Length :	32 cm
Grip design :	Diamond	Thickness :	1.55 mm
Grip :	Dry, Wet, Oil	Color :	Black, Green

**PACKING / TRANSPORT**

---

Sales Units Per Bundle: 6

---

Sales Units Per Outer Case: 36